

# EZ-2PS



## Home and Office Label Printing

Compact in size, user friendly in operation, and capable in printing large volume of direct thermal labels & receipts. With internal flash memory expansion available, you may download more label formats, fonts and graphics for ease of use and convenience. If you are looking for a solution to answer your desktop printing applications, the EZ-2PS is just the right printer to fulfill your needs.

- Page mode printing in direct thermal mode
- 203dpi print resolution
- 2" print width at a print speed of 2ips
- Easy to use Windows "WYSIWYG"
- Internal label roll of 4" OD capacity expandable to 10" external OD capacity
- User replaceable print head
- Built-in serial and parallel ports
- Stripper function as standard
- Optional Real Time Clock
- Optional SRAM and Flash memory



**GODEX**



## EZ-2PS Specifications

<b>Model</b>	<b>EZ-2PS</b>
Resolution	203 dpi (8 dot/mm)
Print Mode	Page Mode Direct Thermal
CPU	16 Bit
Sensor Location	Center aligned
Sensor Type	Reflective, Transmissive
Sensor Detection	Label gap and black mark sensing
Print Speed	50.8mm/sec (2ips)
Print Length	Max. 203mm (8")
Print Width	Max. 56mm (2.20")
Media	Type:Roll-feed, Die-cut, plain paper, and Fan-fold Core:1" core Width:61mm Thickness:0.06mm~0.2mm
Printer Language	EZPL
Software	Application: QLabel-II DLL & Driver: Microsoft Windows 95, 98, Me, NT 4.0, 2000 and XP
Fonts/Resident	Resident Fonts Point Sizes: CG Triumvirate Font 6,8,10,12,14,18,24,30
Fonts	Font Expansion 1-10 Vertical; 1-10 Horizontal
Barcode	Code 39, Code 93, Code 128, UCC 128, UPC A/ E (add on 2 & 5), I 2 of 5, EAN 8 / 13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, MaxiCode and PDF417
Interface	Centronics Parallel Port Buffered I/O Port RS-232C at 4800 to 38400 baud rate DB9 connector XON/XOFF or RTS/CTS Handshaking
Memory	Standard: 256KB SRAM Optional: 1MB or 2MB Flash
Power	AC 13.5V ~ 16V 4 ~ 5A DC 18.0V ~ 24V 4 ~ 5A
Environment	Operation:40° F to 104° F (5° C to 40° C) Storage:-40° F to 122° F (-20° C to 50° C)
Humidity	Operation: 10~90%, non-condensing. Free air.
Cert. Approval	CE, CUL, FCC Class A
Printer Dimension	Depth:127mm (5") Height:215mm (8.5") Width:144mm(5.5") Weight:1.3 Kg
Options	Cutter 1MB or 2MB Flash memory module

Specifications subject to change without notice.